

FORMULARIO FISICA DOS

$$\begin{aligned}
 k &= \frac{1}{4\pi\epsilon_0} = 9 \times 10^9 \text{ N} \frac{\text{m}^2}{\text{C}^2} & N_A &= 6.022141 \times 10^{23} \text{ átomos/mol} \\
 \epsilon_0 &= 8.8542 \times 10^{-12} \frac{\text{C}^2}{\text{Nm}^2} & e &= 1.6022 \times 10^{-19} \text{ C} \\
 m_e &= 9.1094 \times 10^{-31} \text{ Kg} & m_p &= 1.6726 \times 10^{-27} \text{ Kg} \\
 m_n &= 1.67491 \times 10^{-27} \text{ Kg} & eV &= 1.6022 \times 10^{-19} \text{ J}
 \end{aligned}$$

$$\mu_o = 4\pi \times 10^{-7} \text{ Tm/A}$$

Campo Eléctrico y Fuerza Eléctrica

$$\begin{aligned}
 \vec{F} &= \frac{kq_1q_2}{r^2} \hat{r} & \vec{F}_T &= \sum \vec{F} \\
 \vec{E} &= \frac{\vec{F}}{q_o} & \vec{E} &= \frac{kq}{r^2} \hat{r} & \vec{E} &= \int \frac{k dq}{r^2} \hat{r} \\
 dq &= \lambda dl & dq &= \sigma dA & dq &= \rho dV
 \end{aligned}$$

$$E = \frac{\sigma}{\epsilon_0} \quad E = \frac{\sigma}{2\epsilon_0}$$

Dipolo eléctrico

$$p = lq \quad \tau = pE \sin \theta \quad \vec{\tau} = \vec{p} \times \vec{E} \quad U = -\vec{p} \cdot \vec{E} = -pE \cos \theta$$

Flujo eléctrico

$$\Phi_E = \vec{E} \cdot \vec{A} = EA \cos \theta \quad \Phi_E = \oint \vec{E} \cdot d\vec{A} \quad \oint \vec{E} \cdot d\vec{A} = \frac{q_{\text{encerrada}}}{\epsilon_0}$$

Energía Potencial Eléctrica

$$U = \frac{kq_1q_2}{r} \quad U_{\text{sistema}} = \sum U \quad W = -\Delta U$$

Potencial Eléctrico

$$\begin{aligned}
 V &= \frac{U}{q} & V &= \int \frac{k dq}{r} & V &= \frac{kq}{r} & V_T &= \sum V \\
 \Delta V &= -\int \vec{E} \cdot d\vec{l} \\
 E_x &= -\frac{dV}{dx} & E_r &= -\frac{dV}{dr} & \vec{E} &= -\nabla V
 \end{aligned}$$

CAPACITANCIA

$$\begin{aligned}
 C &= \frac{Q}{\Delta V} & \text{placas paralelas } C &= \frac{\epsilon_0 A}{d} \\
 \text{esférico } C &= \frac{ab}{k(b-a)} & \text{cilíndrico } C &= \frac{l}{2k \ln(\frac{b}{a})} \\
 \text{Serie } \frac{1}{C_{eq}} &= \frac{1}{C_1} + \frac{1}{C_2} + \dots + \frac{1}{C_n} \\
 \text{Paralelo } C_{eq} &= C_1 + C_2 + \dots + C_n \\
 U &= \frac{Q^2}{2C} = \frac{1}{2} C \Delta V^2
 \end{aligned}$$

$$\begin{aligned}
 \text{dieléctricos } C &= KC_o & C &= \frac{K\epsilon_0 A}{d} & \Delta V &= \frac{\Delta V_o}{K} \\
 \int \int \vec{E} \cdot d\vec{A} &= \frac{q_{\text{encerrada}}}{\epsilon} & \epsilon &= K\epsilon_0
 \end{aligned}$$

CORRIENTE, RESISTENCIA

$$I = \frac{\Delta Q}{\Delta t} \quad I = \frac{dq}{dt} \quad I = nqA\vec{v}$$

$$J = \frac{I}{A} \quad \vec{J} = nq\vec{v}_d \quad V = IR$$

$$R = \frac{\rho L}{A} \quad \rho = \frac{E}{J}$$

$$\rho(T) = \rho_o [1 + \alpha(T - T_o)]$$

$$P = VI \quad P = Ri^2 \quad P = \frac{V^2}{R}$$

resistencias en serie $R_{eq} = R_1 + R_2 + \dots + R_n$

resistencias en paralelo $\frac{1}{R_{eq}} = \frac{1}{R_1} + \frac{1}{R_2} + \dots + \frac{1}{R_n}$

CIRCUITOS DE CORRIENTE CONTINUA

Leyes de Kirchoff $\sum_{nodo} I_{entran} = 0 \quad \sum_{malla} \Delta V = 0$

circuito simple RC carga $q(t) = CV(1 - e^{-\frac{t}{RC}})$

$$i = \frac{V}{R} e^{-\frac{t}{RC}} = I_o e^{-\frac{t}{RC}} \quad V_C = V(1 - e^{-\frac{t}{RC}})$$

$$\text{Descarga} \quad i = \frac{V_o}{R} e^{-\frac{t}{RC}} \quad q(t) = Q_o e^{-\frac{t}{RC}}$$

MAGNETISMO

$$\vec{F} = q\vec{v} \times \vec{B}$$

Fuerza de Lorentz $\vec{F} = q\vec{E} + q\vec{v} \times \vec{B}$

$$F = I\vec{l} \times \vec{B} \quad \sum F = m\frac{v^2}{R}$$

$$\vec{\tau} = \vec{\mu} \times \vec{B} \quad \vec{\mu} = NiA\hat{n} \quad \tau = \mu B \sin\theta$$

$$U = -\vec{\mu} \cdot \vec{B} = -\mu B \cos\theta$$

FUENTES DE CAMPO MAGNÉTICO

Ley de Biot-Savart $\vec{B} = \frac{\mu_o I}{4\pi} \int \frac{d\vec{l} \times \vec{r}}{r^2}$

Ley de Ampere $\oint \vec{B} \cdot d\vec{l} = \mu_o i_{enc}$

$\mu_o = 4\pi \times 10^{-7} Tm/A$ Conductor largo $B = \frac{\mu_o I}{2\pi r}$

Solenoide $B = \mu_o nI$ $n = \frac{\#vueltas}{Longitud}$

Ley de Gauss $\oint \vec{B} \cdot \hat{n} dA = 0 \quad \varepsilon = -N \frac{d\Phi_B}{dt} \quad \Phi_B = \oint \vec{B} \cdot \hat{n} dA$

$$\varepsilon = \oint \vec{E} \cdot d\vec{l}$$

INDUCTANCIA $\varepsilon = -L \frac{di}{dt} \quad L = \frac{N\Phi_B}{i} \quad U = \frac{1}{2} LI^2$